



KODAK PROFESSIONAL

Inkjet Photo Paper, Lustre / 255g - Dry Lab

Unsurpassed quality in your own studio

Resin-coated paper base

Featuring a true photographic resin-coated base paper and e-surface finish with “pulp of unsurpassed quality,” KODAK PROFESSIONAL Inkjet Photo Paper, Lustre gives you the freedom to print in your studio, and the KODAK PROFESSIONAL back-print seal of quality to back it up. ArtSure certified for quality and archival properties.

Bright white point

KODAK PROFESSIONAL Inkjet Photo Paper, Lustre is compatible with Noritsu, Fuji and Epson Dry Lab printers.

ArtSure Certification

ArtSure Certification ensures the highest standards for fine art prints giving art collectors and artists confidence and validity in limited edition print runs.

APPLICATIONS:

- High-end photographs
- Photo albums, greeting cards, photo books and other Dry Lab applications
- ArtSure Certification certifies testing for archival properties of lightfastness and permanence

FEATURES:

- 10-mil, 255-gram e-surface photo paper
- Microporous, instant-dry coating on a resin-coated paper base
- Compatible with Noritsu, Fuji and Epson Dry Lab printers
- Bright white point provides clean highlight detail
- Thermal and cold laminate compatible

US Size	Euro Size	Quantity	SKU
4" x 328'	10,16 cm x 100 m	4-pack	KPRO4LDL
5" x 328'	12,7 cm x 100 m	4-pack	KPRO5LDL
6" x 328'	15,24 cm x 100 m	4-pack	KPRO6LDL
8" x 328'	20,32 cm x 100 m	2-pack	KPRO8LDL
10" x 328'	25,4 cm x 100 m	2-pack	KPRO10LDL
12" x 328'	30,48 cm x 100m	2-pack	KPRO12LDL



KODAK PROFESSIONAL

Inkjet Photo Paper Lustre / 255g - Dry Lab

Properties	Specifications
Material	Resin-coated photo base
Gauge	10 mil / 255g
Gloss Level	>/=25
Opacity	>90%
Whiteness	>134
Printer/Ink Compatibility	Compatible with Noritsu, Fuji and Epson Dry Lab printers.
Light-fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.
Optimal Service Environment	72° F (21° C), 50% R.H For end use: 0-300° F
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



BMG BRANDmanagementGROUP

AMS: 888-893-4668
EMEA: +34 935 479 700
APJ: +61 2 8038 5013

KodakWFMedia.com

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2017, Brand Management Group

