

FLOOR

GCLS.FG

High quality monomeric PVC textured laminating film. The pressure sensitive adhesive is solvent-free, environment friendly, giving the enhanced benefit of avoiding discoloration of the print or inkjet media. Suitable for use in a wide variety of applications including various floor graphics (fulfills anti-slip standard DIN 51130 - R10 Rating), as well as pop-up materials.

FEATURES

Monomeric PVC-film, outdoor durability up to 1 years
One-side coated adhesive, polyacrylate, solvent-free, pH-neutral, age resistant
The adhesive provides excellent adhesion to printed media incl. UV-Inkjet printed materials
Single side siliconized release paper
Fulfills anti-slip standard DIN 51130 „R10 Rating“
3 month durability for floor graphics

PHYSICAL PROPERTIES

Carrier	Soft-PVC-film, 100µm, monomeric
Total Thickness	120 µm
Surface	Textured
Adhesive	Solvent free, polyacrylate, permanent
Liner	Single side siliconized glassine paper, white, 63 g/m ²
Peel adhesion	11 (AFERA 5001)

ENVIRONMENTAL CONDITIONS

Operating	8°-40°C
Storage	18°-22°C (50-60% rH non condensing)

AVAILABLE SIZES

65 cm x 50 m
104 cm x 50 m
140 cm x 50 m
155 cm x 50 m

ADDITIONAL INFORMATION

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme condition (tropical climate, desert climate, high humidity, high UV-light exposure or polluted areas) may cause rapid deterioration.

Please include always the batch number to questions about the product or complaints.
(see inside sleeve)

Specifications subject to change without notice.
All trademarks are the property of their respective companies.